



Description & Features:

- Designed to be welded in place within the system
- Economical
- 1 year warranty

Applications:

- Tanks or feed water system on boilers where no internal threads are available

Specifications

Material	304 or 316 SS
Thermometer Connection	1/2" NPT
Bore	0.260" (6.5mm) standard

Order Codes

Stem Length	Pipe Diameter	Dimension P	Dimension Q	Dimension U	Material	Code
4" (100mm)	3/4"	1.05" (27mm)	1/2" (12.5mm)	2.5" (63mm)	304 SS	TWS754304
		1.315" (33mm)	7/8" (22mm)		316 SS	TWS754316
	1"	1.05" (27mm)	3/4" (19mm)		304 SS	TWS14304
		1.315" (33mm)	7/8" (22mm)		316 SS	TWS14316
6" (150mm)	3/4"	1.05" (27mm)	3/4" (19mm)	4.5" (115mm)	304 SS	TWS756304
		1.315" (33mm)	7/8" (22mm)		316 SS	TWS756316
	1"	1.05" (27mm)	3/4" (19mm)		304 SS	TWS16304
		1.315" (33mm)	7/8" (22mm)		316 SS	TWS16316
9" (230mm)	3/4"	1.05" (27mm)	3/4" (19mm)	7.5" (191mm)	304 SS	TWS759304
		1.315" (33mm)	7/8" (22mm)		316 SS	TWS759316
	1"	1.05" (27mm)	3/4" (19mm)		304 SS	TWS19304
		1.315" (33mm)	7/8" (22mm)		316 SS	TWS19316
12" (300mm)	3/4"	1.05" (27mm)	3/4" (19mm)	10.5" (267mm)	304 SS	TWS7512304
		1.315" (33mm)	7/8" (22mm)		316 SS	TWS7512316
	1"	1.05" (27mm)	3/4" (19mm)		304 SS	TWS112304
		1.315" (33mm)	7/8" (22mm)		316 SS	TWS112316

Other configurations available.

