



Description & Features:

- Low and high pressure gauge kit in a protective plastic blow molded case
- Re-zero with external recalibration screw
- Plastic blow molded case for added durability
- Sleek design featuring secure latch
- Pump and fitting for simplified and quick connections
- ASME B40.100 compliant
- CRN registered
- 5 year warranty

Applications:

- Portable leak and loss of pressure detection unit for gas and water lines

Specifications	Gas Test Gauge (1)	Water Test Gauge (2)
Dial	2.5" (63mm) white aluminum with black markings	2" (50mm) white aluminum with black markings
Case/Ring	Steel, painted black with steel ring	Steel, painted black
Lens	Polycarbonate snap in	Polycarbonate
Connection	Rubber hand pump with hose and mini ball valve with handle and 1/2" NPTF x 1/4" NPTF test block and 1/2" NPTM x 1/2" NPTM nipple	3/4" NPTF x M8x0.8 test block with cap
Pressure Range	0/5 psi	0/160 psi
Movement	Engineered plastic upper and lower plate with brass pinion and sector	Brass
Pointer	Aluminum, anodized black	Aluminum, black
Ambient Temperature	-40°F to 150°F (-40°C to 65°C)	-40°F to 150°F (-40°C to 65°C)
Accuracy	±3-2-3% ANSI/ASME Grade B	±3-2-3% ANSI/ASME Grade B
Enclosure Rating	IP52	IP52
Case	Plastic blow molded (11.875" x 18")	
Warning	WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .	

Order Codes (products in bold are normally stock in North America)

Kit	Additional Hand Pump
PGWT0100	PHPT0100