








## Winters Valve Questionnaire

<b>Type:</b>			
NVA <input type="checkbox"/>		NVA Multiport <input type="checkbox"/>	
B&B 1 Handle <input type="checkbox"/>		B&B 2 Handles <input type="checkbox"/>	
Double B&B <input type="checkbox"/> 			
<b>Body Type:</b> Straight <input type="checkbox"/> Angle <input type="checkbox"/>			
<b>Connection Size:</b>			
Process: 1/4" <input type="checkbox"/> 3/8" <input type="checkbox"/> 1/2" <input type="checkbox"/> 3/4" <input type="checkbox"/> 1" <input type="checkbox"/> Other			
Instrument: 1/4" <input type="checkbox"/> 3/8" <input type="checkbox"/> 1/2" <input type="checkbox"/> 3/4" <input type="checkbox"/> 1" <input type="checkbox"/>			
NPT <input type="checkbox"/> BSP <input type="checkbox"/> Other _____			
<b>Process Connection Type:</b> Male <input type="checkbox"/> Female <input type="checkbox"/>			
<b>Body Material:</b>			
CS <input type="checkbox"/> SS <input type="checkbox"/> NACE <input type="checkbox"/> Other _____			
<b>Seat Type:</b> Hard Seat <input type="checkbox"/> Soft Seat <input type="checkbox"/>			
<b>Pressure Rating:</b>			
6,000 psi <input type="checkbox"/> 10,000 psi <input type="checkbox"/> Other _____			

Note: When selecting valves, refer to ASME B31.3, ASME B31.1, ASME B16.34 and ANSI MSS SP-99