Catalogue Page	Series	Dial Size								Scale Size					Case Material					Wetted Parts		Connec-tion Size			Accuracy						
		≤2"	2.5"	3"	3.5"	4"	4.5"	5"	≥6"	4.5"	5"	6"	8"	9"	Steel	SS	Aluminum	Valox®*	Plastic	Brass	SS	1/4" NPT	1/2" NPT	3/4" NPT	1% (Grade A)	2% (Grade B)	2.5% (Grade B)	3% (Grade B)	With thermowell	RoHS compliant	Lead Free Option
195	TAG HVAC Gold Case Thermometer									x		x					x			x	x		x			x			x		
197	TAS/TAS-LF Industrial/Lead Free Industrial 5" Thermometer										x								x	x			x			x			x	x	x
199	TBM Bi-Metal Thermometer	x		x		x		x	x							x					x	x	x		x					x	
204	TBT HVAC Bi-Metal Thermometer				x										x					x			x				x				
205	TCT Clamp-On Thermometer		x												x													x			
206	THR HVAC Remote Reading Thermometer	x	x													x				x							x				
208	THS Solar Digital Bi-Metal Thermometer			x												x					x		x		x					x	
209	TIM/TIM-LF Industrial/Lead Free Industrial 9" Thermometer													x			x	x		x				x	x				x	x	x
211	TMT Surface Magnet Thermometer	x													x											x					
212	TNR Food & Beverage Bi-Metal Thermometer			x												x					x		x		x					x	
213	TRR Gas or Vapour Remote Reading Thermometer		x		x	x	x		x						x	x	x			x	x		x	x	x	x				x	
219	TSD Industrial Solar Digital									x									x	x				x	x				x	x	
221	TSW/TSW-LF Hot Water/Lead Free Hot Water Thermometer	x	x										x		x		x			x			x		x				x		x
223	TTD Tridicator		x	x											x					x		x	x					x			

Valox® is a registered trademark of the General Electric Company

Note: When selecting a thermometer, always refer to ASME B40.200 (2008)