

Catalogue Page	Series	Dial Size											Scale Size					Case Material				Wetted Parts		Connection Size			Accuracy				With thermowell	RoHS compliant	Lead Free Option	
		≤2"	2.5"	3"	3.5"	4"	4.5"	5"	≥6"	4.5"	5"	6"	8"	9"	Steel	SS	Aluminum	Valox®	Plastic	Brass	SS	1/4" NPT	1/2" NPT	3/4" NPT	1% (Grade A)	2% (Grade B)	2.5% (Grade B)	3% (Grade B)						
192	TAG HVAC Gold Case Thermometer								X		X					X			X	X		X			X									
194	TAS/TAS-LF Industrial/Lead Free Industrial 5" Thermometer									X								X	X			X			X			X		X	X			
196	TBM Bi-Metal Thermometer	X		X		X		X	X							X				X	X	X	X	X						X				
201	TBT HVAC Bi-Metal Thermometer				X									X						X			X			X								
202	TCT Clamp-On Thermometer		X											X													X							
203	THR HVAC Remote Reading Thermometer	X	X													X				X							X							
205	THS Solar Digital Bi-Metal Thermometer			X												X				X		X		X							X			
206	TIM/TIM-LF Industrial/Lead Free Industrial 9" Thermometer											X				X	X		X					X	X				X	X	X			
208	TMT Surface Magnet Thermometer	X													X											X								
209	TNR Food & Beverage Bi-Metal Thermometer			X												X				X		X		X							X			
210	TRR Gas or Vapour Remote Reading Thermometer		X		X	X	X		X					X	X	X				X	X		X	X	X	X					X			
216	TSD Industrial Solar Digital								X									X	X					X	X				X	X				
218	TSW/TSW-LF Hot Water/Lead Free Hot Water Thermometer	X	X								X			X		X				X			X		X			X				X		
220	TTD Tridicator		X	X											X					X		X					X							

Valox® is a registered trademark of the General Electric Company

Note: When selecting a thermometer, always refer to ASME B40.200 (2008)